

870 CARBON BLOCK PREMIER



Product Specification



CHLORAMINE GRADE CARBON



37°C



sfwt.eu/pcb



Ordering Details

| Product Code | Micron (µm) | Standard Lengths (") | Capacity Chloramine Removal (litres) @ Flow Rate (lpm) (3ppm to 0.5ppm) |
|--------------|-------------|----------------------|---|
| PCB | 1 | 9¾ | 15,000 @ 1.9 |
| | | 20 | 30,000 @ 3.8 |
| | | 30 | 45,000 @ 7.6 |
| | | 40 | 60,000 @ 11.4 |
| | | 9¾BB | 50,000 @ 7.6 |
| | | 20BB | 100,000 @ 15.2 |



e.g. PCB-1-20BB

| Packaging | 9¾" | 20" | 30" | 40" | 9¾"BB | 20"BB |
|-----------|-----------|------------|------------|------------|----------|-----------|
| | 15 at 7kg | 15 at 14kg | 15 at 21kg | 15 at 28kg | 6 at 7kg | 6 at 14kg |

Features & Information

- Outstanding chloramine and chlorine reduction
- Manufactured from FDA compliant materials
- Extruded block constructed from premier grade carbon for high purity and greater surface area than traditional carbon blocks
- Low pressure drop across the range
- Outer polypropylene wrap protects and extends the life of the block by preventing premature plugging