

Part Number: ZVF 50 JET.1 SIC ER 583 GKG38 EKG1200



© ELAFLEX HIBY, Hamburg / Germany



<https://nozzleconfigurator.elaflex.co.uk/NON AUTO AIR/3484/24866/24868/24880/24878/24936/24896/24961/24945/Product11.html>

| | |
|-----------------------|--|
| Nozzle Type | <p>ZVF 50 Manually operated nozzle DN 50 Manual aviation fuelling nozzle without automatic shut-off function for overwing service. For AVGAS and JET-fuels. Max. flowrate 400 l/min. (85 IGM - higher flowrates are possible). Size DN 50</p> |
| Body | <p>ZVF 50 JET For JET fuels</p> |
| Hose Inlet | <p>DG 50.1 AF AI black 1½" BSP male Easy-rotating swivel. For petroleum based products, i.e. aircraft refuelling (ZVF 50).</p> |
| Spout Connection | <p>Screw-In-Connection Standard type Screw-In-Connection (SIC) for spouts.</p> |
| L-Type | <p>Standard Suitable for pressure service with a pump.</p> |
| Sight Glass | <p>Without sight glass Without</p> |
| Spout | <p>DN 38 Spout ID 38 mm, OD 44 mm. max. 400 l/min.</p> |
| Dust Cap Assembly | <p>With GKG 38 Dust Cap Assembly GKG 38 Dust cap assembly. Cap NBR, chain and spring brass and bronze.</p> |
| Ground Cable Assembly | <p>With EKG 1200 Ground Cable Assembly EKG 1200 With brass clamp, and plastic coated steel wire.</p> |



1200 mm standard length.
Assembly is mounted by Elaflex.

PDF Documents

-  Page 541a-d (ZVF 50)
-  Page 363-364 (DG 50.1 AF AI black)

Contact:

ELAFLEX Limited
Riverside House,
Plumpton Road
Hoddesdon, Herts EN11 0PA
United Kingdom
Phone No.: +44 (0)1992 452 950
Internet: www.elaflex.co.uk